

# PRODUCT INFORMATION

## Protect All, Inc.

1910 E. Via Burton Street  
Anaheim, California 92806-1215  
Toll Free 800 322-4491 • 714-635-4491  
FAX 714-635-9716  
www.protectall.com

*Manufacturer of Cutting Oils, Lubricants, Rust Preventatives and other Industrial Products*

### Champions Choice

## CHAIN LIFE (The Original, Since 1967)

### LUBRICANT

#### Description

Chain Life is a unique foaming lubricant that starts where oil leaves off. The aerosol application applies as a bead of foam thus eliminating overspray and waste. Chain Life leaves a thin thermally stable film of extreme pressure lubricant that provides a barrier between moving metal parts, preventing metal to metal contact under heat and pressure. Chain Life lubricates, penetrates, clings and silences chains while repelling the excess accumulation of dirt, sand, mud and grass. It does not contain moly, silicone or graphite.

Chain Life is also excellent as a tapping and threading compound, a lubricant for clutch shafts and open gear systems, a pre-assembly lube for engine parts, as well as an all-around general purpose lubricant. It is available as a liquid in larger containers.



#### Laboratory Data

##### Typical Neat Properties

|            | SSU @<br>100°F | SSU @<br>210°F | cSt @<br>40°C | Flash Point<br>COC, °F | Pour Point<br>°F |
|------------|----------------|----------------|---------------|------------------------|------------------|
| Chain Life | 325            | 54             | 68            | >400                   | 30               |

#### Falex Test indicates the effectiveness of Chain Life as a lubricating medium.

On the Falex Test, oil fails at 17 in./lbs. of torque under a 500 pound jaw load. The extreme pressure and anti-friction agents used in Chain Life produce Falex results of 45 in./lbs. of torque with a 3700 lb. jaw load.

Refer to Protect All, Inc. (formerly Champions Choice, Inc.) Material Safety Data Sheet for complete health and safety information.

The Information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Protect All, Inc. or others is not to be inferred from any statement contained herein. 3/08